



SWiFT CTD

CTD Profiler

Designed from the outset with the intention of a seamless workflow, the SWiFT CTD profiler provides survey-grade sensor technology coupled with the convenience of Bluetooth® wireless technology and rechargeable batteries. An integral GNSS module, to geo-locate each profile, completes the package. Data can be easily and quickly downloaded and reviewed wirelessly via Bluetooth connectivity using Teledyne Valeport's Ocean software for Windows, iOS or Android. Data can be instantly shared, in industry standard data formats through email and cloud services. A USB Cable and Bluetooth adapter are provided.

In addition to the directly measured Conductivity, Temperature and Depth measurements, Salinity, Density and Sound Velocity are calculated using the UNESCO international standard algorithm and Chen and Millero equation. With a large internal Lithium-ion rechargeable battery and the convenience of charging via USB, the SWiFT CTD is intended for offshore, coastal, harbour and inland environmental and hydrographic survey use to 500 m and offers the highest quality CTD profiles in a compact, robust and portable package.

Optionally, there is a deployment cage available to bolt onto the instrument to help get the SWiFT CTD to depth in fast-flowing currents.

DATA SHEET

Product Details



MULTI-PARAMETER
CTD



SOUND
SPEED



OCEAN & CONNECT
PATHWAY EDITION
SOFTWARE



USB



RECHARGEABLE
BATTERY



GNSS

Sensor Specifications

The SWiFT CTD is fitted with Teledyne Valeport's conductivity sensor, temperature compensated piezo-resistive pressure transducer and a new fast response thermistor temperature sensor.

Conductivity

Range	0-80 mS/cm
Resolution	0.001 mS/cm
Accuracy	±0.01 mS/cm

Temperature

Range	-5°C – +35°C
Resolution	0.001°C
Accuracy	±0.01°C

Pressure

Range	50 Bar
Resolution	0.001% FS
Accuracy	±0.01% FS

Calculated Parameters and Accuracy

Calculations based on the UNESCO international standard algorithm and Chen and Millero equation

Sound Velocity	~0.25 m/s
Salinity	±0.01 PSU
Density	±0.01 kg/m ³

Physical

Materials	Housing - Titanium Sensor Guard - Acetal Temperature Sensor - Titanium Pressure Sensor - Titanium Conductivity Sensor - Polyurethane coated titanium with ceramic core
Depth Rating	500 m
Dimensions	ø78 mm x Length 350 mm
Weight	2.7 kg (in air) / 1.65 kg (in water)



Communications (set up and data offload)

USB Serial

Bluetooth v4	Low energy
--------------	------------

Electrical

Battery	Internal rechargeable Li-ion battery pack
Battery life	SWiFT Battery endurance depends on the sampling scenario used – contact Valeport for more information. 100 days endurance 5 profiles per day to 100 m* 70 days endurance 3 profiles a day to 500 m* 5 days continuous running (normal power mode) (*Utilising Bluetooth Sleep mode)
Charging	USB Typically, 1 hour fast charge will give 12 hours operation

Software

iOS and Android Teledyne Valeport Connect Pathway Edition for Bluetooth compatible mobile devices – instrument set up, data offload, display and translation to common data formats. Teledyne Valeport's Ocean PC software, with both USB cable and Bluetooth connectivity, for instrument setup, data extraction, display and translation to common data formats.

Instrument and data time is synchronised to GNSS, UTC.

Ordering

0660049-50	SWiFT CTD Profiler Titanium housing rated to 500 m
Supplied with	PC Bluetooth adapter USB interface and charging cable 1.5 A charger Teledyne Valeport Ocean software Operating manual System transit case



The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by Teledyne Valeport Ltd is under license. Other trademarks and trade names are those of their respective owners.

Datasheet Reference: SWiFT CTD | December 2024

As part of our policy of continuing development, Teledyne Valeport Ltd. reserve the right to alter at any time, without notice, all prices, specifications, designs and conditions of sale of all equipment - Teledyne Valeport Ltd © 2024