



SWiFT SVPplus Phycocyanin

Multi-parameter profiler

Cyanobacteria (or blue-green algae) are photosynthetic bacteria that occur naturally in surface waters. Under certain conditions of light, temperature and nutrient levels cyanobacteria can multiply rapidly, forming a bloom. Some Cyanobacteria produce toxins which pose health risks for humans and animals. The EU Bathing Waters Directive therefore requires monitoring for these blue-green algae blooms.

Testing for the actual toxins is possible by means of laboratory analysis of water samples, but this can be costly and time-consuming. However, cyanobacteria contain a fluorescent pigment called Phycocyanin, which can be detected in real time using a Valeport SWiFT SVPplus Phycocyanin fluorometer. The Valeport SWiFT SVPplus Phycocyanin uses narrow bandpass filters on both excitation and emission wavelengths to ensure that the response is specific to Phycocyanin and not affected by false positive results from normal Chlorophyll a fluorescence.

DATA SHEET

Product Details



MULTI-PARAMETER CTD



SOUND SPEED



OPTICAL



OCEAN & CONNECT PATH-
WAY EDITION
SOFTWARE



USB



Rechargeable
Battery



GNSS

Valeport Limited
St. Peters Quay, Totnes,
Devon TQ9 5EW United Kingdom

Telephone: +44 (0) 1803 869292
Email: sales@valeport.co.uk
www.valeport.co.uk



Valeport's Hyperion Fluorometer sensor range, when combined with SWiFT, delivers high performance measurements of Phycocyanin in a compact & robust package.

Sensor Specification

Phycocyanin*	
Excitation	590 nm
Detection	650 nm
Dynamic Range	0-9,000 ppb 2 gain settings: 0-50, 0-9,000 software controlled
Minimum Detection (3x SD in RO water)	<0.08 ppb
Linearity	0.99 R ²
Response Time	0.03 to 2 sec
Output Rate	0.5 Hz to 32 Hz (free running) software controlled
Conductivity#	
Range	0 - 80 mS/cm
Resolution	0.001 mS/cm
Accuracy	±0.05 mS/cm
Temperature (Platinum Resistance Thermometer)	
Range	-5°C – +35°C
Resolution	0.001°C
Accuracy	±0.01°C
Pressure (Temperature compensated piezo-resistive pressure transducer)	
Range	50 Bar
Resolution	0.001% FS
Accuracy	±0.01% FS
Sound Velocity (Digital time of flight sensor)	
Range	1375 – 1900 m/s
Resolution	0.001 m/s
Accuracy	±0.02 m/s
Salinity#	
Range	0 - 42 PSU
Resolution	0.001 PSU
Accuracy	±0.05 PSU
Density	
Range	990 - 1035 kg/m ³
Resolution	0.001 kg/m ³
Accuracy	±0.05 kg/m ³

*Calibrated against Phycocyanin in water/Phosphate buffer solution.

#Calculated Accuracies. Calculations based on Valeport's proprietary DASH formula.

Physical dimensions

Materials	Housing: Titanium
	Sinker weight: Stainless steel
	Optical window: Sapphire glass
Depth rating	500m
Dimensions	Ø78mm x Length 307mm (with sinker weight)
Weight	2.7kg (in air) / 1.7kg (in water) including optional sinker weight

Communications (set-up and data offload)

Bluetooth® v4 - low energy

USB Serial

Electrical

Battery	Internal rechargeable Li-ion battery pack
Charging	USB - Supplied mains AC adapter

Software

iOS and Android Valeport Connect Pathway Edition for Bluetooth compatible mobile devices – instrument set up, data offload, display and translation to common data formats. Valeport's Ocean PC software, with both USB cable and Bluetooth connectivity, for instrument setup, data extraction, display and translation to common data formats.

Instrument and data time is synchronised to GNSS, UTC.

Ordering

0660047-50-FP	SWiFT SVPplus profiler with Phycocyanin sensor 500m rated
Supplied with	PC Bluetooth adapter USB interface and charging cable 1.5 A charger Valeport Ocean software Operating manual System transit case



Datasheet Reference: SWiFT SVPplus Phycocyanin | February 2023

As part of our policy of continuing development, Valeport Ltd. reserve the right to alter at any time, without notice, all prices, specifications, designs and conditions of sale of all equipment - Valeport Ltd © 2023

